

Steel Construction New Zealand

Slab Panel Method Workshop



**An afternoon seminar for
Design Engineers and
Regulatory Authorities**

**Auckland 2nd September 2014
Christchurch 9th September 2014**

About the Presenters

Dr Charles Clifton, University of Auckland



Charles has specialised in structural steel and composite engineering since joining the University of Auckland in 2008. This followed a productive period since 1983 as Senior Structural Engineer at the Heavy Engineering Research Association, where he conducted research in structural steel, composite construction, fire engineering and durability. He also made considerable contributions to the introduction of new and revised standards, developed widely used design guides and was actively involved in professional development. A long and productive collaboration with the University of Auckland saw many innovations researched, developed and adopted by the profession, and also saw the award of his PhD in 2005.


Charles is a Fellow of the Institute of Professional Engineers New Zealand and of the National Society for Earthquake Engineering. He is currently active in a range of research projects involving the development of low-damage seismic solutions, performance of composite steel floors in severe fires, and floor and frame solutions using light gauge steel members and components.

Dr Anthony Abu, University of Canterbury




Dr. Anthony Abu is the New Zealand Fire Service Commission Lecturer in Fire Engineering at the University of Canterbury. Tony obtained his Bachelor's degree in Civil Engineering from Eastern Mediterranean University, North Cyprus and then completed his PhD in Structural Fire Engineering at the University of Sheffield, UK, on the behaviour of composite floor slabs in fire.

He has been involved in the implementation of the structural fire engineering Eurocodes in the UK and also worked on a number of structural, and structural fire engineering projects, including a number of sports stadia, office complexes and airports, during a brief period with Buro Happold Engineers Ltd. UK.



Development of the Slab Panel Method

By G Charles Clifton,
University of Auckland
and
Anthony Abu
University of Canterbury





1




Scope of Presentation: SPM Development

- Basis of design procedure
- Structural performance to be delivered
- Building structure characteristics and detailing requirements
- Background to procedure development
- Future research planned




2



Basis of Design Procedure

Under ambient temperature conditions:

- The beams support the floor slab
- One way action prevails
- Load path:
slab → 2^o beams → 1^o beams → columns



Under severe fire conditions:

- Unprotected secondary beams lose strength
- Two way action prevails (slab panel)
- Slab panel supports the beams
- Load path : slab panel → supporting beams → columns
- Slab panel axial forces are in in-plane equilibrium

THE UNIVERSITY OF AUCKLAND FACULTY OF ENGINEERING

UC UNIVERSITY OF CANTERBURY Te Whare Wānanga o Waitaha


3

SCNZ STEEL CONSTRUCTION NEW ZEALAND

Structural Performance to be Delivered by the Procedure - 1 of 2

Under severe fire conditions:

- Slab and secondary beams may undergo appreciable deformation
- Support beams and columns undergo minimal deformation
- Tensile membrane response may be activated
- Load-carrying capacity and integrity are preserved for calculated t_e or specified FRR
- Insulation is met for required period



THE UNIVERSITY OF AUCKLAND FACULTY OF ENGINEERING

UC UNIVERSITY OF CANTERBURY Te Whare Wānanga o Waitaha

4

SCNZ STEEL CONSTRUCTION NEW ZEALAND


Structural Performance to be Delivered by the Procedure - 2 of 2


Suppression of structural damage controlled by:

- Shielding linings (limited effectiveness)
- Sprinkler protection (extremely effective)


Effective compartmentation is maintained:

- Between floors
- Between firecells, same floor






5





Building Structure Characteristics Required for Implementation of Slab Panel Design Procedure

(1) Floor slabs


- concrete: structural grade, NWC or LWC
- mesh/reinforcement: within slab panel, any grade over supports $\geq 15\%$ uniform elongation
- solid slabs, trapezoidal and clipped pan deck shapes







6



Building Structure Characteristics Required for Implementation of Slab Panel Design Procedure

- (2) Steel beams
 - UB, WB, light steel joists, cellular beams
- (3) Columns
 - UC, WC require passive protection in many applications, can use CFSTs
 - Columns in car parking buildings typically don't require passive protection
- (4) Connections
 - must maintain integrity during heating and cooling down
 - connector failure (bolts or welds) to be suppressed
 - same detailing as required for earthquake; NZ standard practice
- (4) Overall building stability
 - no limitations on lateral load resisting systems
 - building stability not endangered by use of SPM

Detailing Requirements

- (1) Floor slab
 - Decking fastened to beams; typically composite
 - Slab tied to edge beams
 - Shear failure at supports suppressed by shear reinforcement
- (2) Protection to slab panel edge support beams
 - When specified, apply over full length
 - Details given for application around connections to secondary beams
- (3) Protection to columns when needed
 - Apply over full length

Detailing Requirements

9

Detailing Requirements

10

Steps to Implementing a Slab Panel Design

First design the floor and structural system for gravity and lateral loading conditions, then:

- Step 1:** Determine the size of the slab panel and location of the slab panel supports
- Step 2:** Determine which of the internal supports can carry negative moment
- Step 3:** Start with recommended reinforcement contents
- Step 4:** Input all variables and check capacity; increase as recommended in report

Fig. 1 Reflected Floor Plan for Application of Slab Panel Fire Engineering Design Procedure to a Concrete Slab on Profiled Steel Deck Supported on Primary and Secondary Beams

11

Moment/Tensile Membrane Resistance

This uses the modified Bailey model, ie:

$$W^* = G + Q_C \text{ from Loadings Standard}$$

$$W_u = (W_{y\theta} - W_{y\theta,ss}) + W_{y\theta,ss}e$$

$$W_u \geq W^* \text{ required}$$

where:

- W^* = fire emergency distributed load
- W_u = slab panel load carrying capacity
- $W_{y\theta}$ = yieldline load carrying capacity in fire
- $W_{y\theta,ss}$ = simply supported yieldline load carrying capacity in fire
- e = tensile membrane enhancement factor
 $= \text{fn}(L_x, L_y, m_x, m_y, t_e, t_o, h_{rc}, f_{y,r,\theta}, E_{y,r,\theta})$
- t_o, h_{rc} are slab thickness, deck rib height
- $f_{y,r,\theta}, E_{y,r,\theta}$ are for reinforcement including secondary beams

12

Shear Resistance


This is additional to the Bailey model:

$$w^* = G + Q_u$$


$$v^* = w^*(L_x / 2)$$

$$V_{u,slab} = \phi_{fire} V_c d_v$$


ϕ_{fire} = 0.89 from standard
 V_c = conc. slab shear capacity
 d_v = effective shear depth
 $V_{u,\theta, sb}$ = shear capacity of secondary beam in fire
 S_{sb} = spacing of secondary beams

$$V^* \leq V_{u,slab} + \frac{V_{u,\theta, sb}}{S_{sb}} \text{ required}$$


Section A-A Through Critical Cross-Section for Shear




THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING



UC
UNIVERSITY OF CANTERBURY
To Whare Wananga o Waitaha


13




SCNZ STEEL CONSTRUCTION
NEW ZEALAND

Development Work Undertaken

- 22 stage experimental and analytical development programme undertaken
- Steps presented in following slides
- Covers from 1995 to 2014




THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING



UC
UNIVERSITY OF CANTERBURY
To Whare Wananga o Waitaha


14



SCNZ STEEL CONSTRUCTION
NEW ZEALAND


Step 1: Cardington Fire Tests 1995/1996 (and 2003)

- Demonstrated performance of large scale composite floor systems
- Showed systems with unprotected beams and protected columns have high fire resistance




Step 2: BRE Design Model and Test 2000

- Colin Bailey Tensile Membrane Model, UK BRE
- Large scale ambient temperature tests on lightly reinforced slabs to validate behaviour



Step 3: First Edition of SPM 2001

- Generalised application of Bailey model for review
- HERA DCB No 60, February 2001
- Incorporating moment capacity of secondary beams
- General formula for yieldline determination
 - includes support moment contribution
- Limits on application set by Bailey for:
 - integrity
 - maximum deflection



HERA
 11-12 Stables Street
 Waiwera City
 Auckland 1021
 Phone: 09 423 9700
 Email: hera@hera.org.nz

February 2001

Introduction

This book presents a simplified design procedure for the design of multi-story steel framed buildings with significant secondary beams of steel for moment-resisting structures in severe fires. The publication of this procedure was developed as part of a programme of research supported by the New Zealand Fire Service for the New Zealand Fire Service.

The design method presented herein is based on the concept of the slab panel-beam moment-resisting frame (SPMRF) for the fire design. Research undertaken and reported in a previous issue of the DCB No 60, has shown that the design method presented herein is a valid design method for the fire design of steel framed buildings in severe fires.

The length of the procedure and the supporting documentation is such that this is the only volume in the book. The first issue presented will cover the design of the building.

Subject Index for 2001 and Prior Issues


A full subject index covering the six issues to date is published with this issue. It is the only one ever published by the Institute of Structural Engineers (I.S.E.)

The new code and the new design procedure will be published in the HERA DCB No 60 at a later date.


Access the web site at the above address and follow the instructions on the site.

Heretape - Information Publications - 0018

HERA - Information Publications - 0018




THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING



UC
UNIVERSITY OF CANTERBURY
Te Whare Wananga o Waitaha

17




SCNZ STEEL CONSTRUCTION NEW ZEALAND


Step 4: FEM of Cardington Test Building 2002 published 2004

- Modelling of Cardington BRE large scale fire test
- Set of interlinked composite beams
- Interlinking required to obtain good agreement with experimental deflected shape
- Showed the two way nature of the floor system behaviour must be considered to replicate experimental behaviour

BRE large compartment test




THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING



UC
UNIVERSITY OF CANTERBURY
Te Whare Wananga o Waitaha

18




SCNZ STEEL CONSTRUCTION NEW ZEALAND

Step 5: Furnace Testing of Six Slab Panels 2001/2002

- part of PhD research project (Linus Lim)
- details as shown opposite and below
- all slabs withstood 180 minutes ISO fire without failure: see next slide

Slab	Thickness	Mesh	
1	661 flat slab	100mm	661 mesh
2	HD12 flat slab	100mm	HD12 bars
3	D147 flat slab	100mm	D147 mesh
4	Hi-bond slab	130 mm	D147 mesh
5	Traydec slab	130 mm	D147 mesh
6	Speedfloor slab	90 mm	661 mesh



Results of tests



D147 top surface crack pattern


Slab	Applied load, w (kPa)	Ambient temperature		At 3 hours in the ISO fire			
		$w_{u,o}$ (kPa)	Load ratio, r_{load}	Max. Steel Temp. ($^{\circ}$ C)	$w_{u,r}$ (kPa)	Load ratio, $r_{load,r}$	
1	661 Flat slab	5.40	20.0	0.270	683	2.40	2.25
2	HD12 Flat slab	5.40	28.2	0.191	688	6.49	0.83
3	D147 Flat slab	5.40	13.3	0.406	703	1.47	3.67
4	Hibond slab	5.52	70.2	0.079	672	1.09	5.06
5	Traydec slab	6.12	75.0	0.082	339	8.57	0.71
6	Speedfloor	5.16	55.1	0.094	623	2.02	2.55

Load ratio $\leq 1.0 \Rightarrow$ no tensile membrane enhancement required

Load ratio $> 1.0 \Rightarrow$ tensile membrane enhancement is required

Step 6: Second Edition of SPM 2002/2003

- Incorporating results of furnace tests
- HERA DCB No 71, February 2003
- Improved determination of slab and reinforcement temperatures
- Revised reinforcement limits for integrity
- Relaxation of maximum deflection and limits on e




No. 71
The second edition of the Bulletin is issued in the February 2003 issue.


December 2002/January 2003
The new design guidance is based on the latest test results and is intended to be used in conjunction with the Bulletin to provide a complete design solution.

Introduction
Almost all of the issues in Bulletin No. 71 are covered in the second edition of the Bulletin. The new design guidance is based on the latest test results and is intended to be used in conjunction with the Bulletin to provide a complete design solution.


On-Line Design & Construction Bulletin Is Now Available
Pages 6 to 14 of DCB No. 68 contain an article that covers all the current guidance presented in the DCB. This is the first time for Australasia that the design guidance is available online, where the design guidance is available.

On-Line Issues	Pages
Structural Design & Construction Bulletin	1
Structural Design & Construction Bulletin	2
Structural Design & Construction Bulletin	3
Structural Design & Construction Bulletin	4
Structural Design & Construction Bulletin	5
Structural Design & Construction Bulletin	6
Structural Design & Construction Bulletin	7
Structural Design & Construction Bulletin	8
Structural Design & Construction Bulletin	9
Structural Design & Construction Bulletin	10
Structural Design & Construction Bulletin	11
Structural Design & Construction Bulletin	12
Structural Design & Construction Bulletin	13
Structural Design & Construction Bulletin	14






21





Step 7: Development and Validation of FE Model 2003


- 6 test slab panels modelled
- Best fit to mid-span deflection made for each case
- Accuracy of models also compared with:
 - reinforcement strains
 - edge deflections and rotations

Example shown for Speedfloor slab










22



Step 8: Determining the Influence of Deforming Supports on Slab Panel Behaviour 2004

FEM used to extend experimental testing to determine the influence of:

- effect of deformation in slab panel edge supports (no effect on capacity; increases panel midspan deformation, 65% contribution)
- horizontal axial restraint is significant, even at low levels (100kN/m stiffness)
- slabs of 4.15m x 3.15m, 8.3m x 6.3m and 8.3m x 3.15m analysed: 8.3m x 6.3m result shown below

CENTRAL SAGGING - L/75
 CENTRAL SAGGING - RIGID SUPPORTS
 LONGER SPAN (8.3m MID NODE - L/75
 SHORTER SPAN (6.3m MID NODE - L/75
 XMIN 0.000E+00
 XMAX 1.800E+02
 YMIN -6.894E-01
 YMAX 1.384E-36

THE UNIVERSITY OF AUCKLAND
 FACULTY OF ENGINEERING

UC UNIVERSITY OF CANTERBURY
 Te Whare Wananga o Waitaha

23

SCNZ STEEL CONSTRUCTION NEW ZEALAND

Step 9: Confirming the SPM Assumption on Secondary Beam Contribution to Slab Panel Behaviour 2004/2005

FEM used to extend experimental testing to determine the contribution of the unprotected secondary beams: contribute to slab panel moment resistance as shown below

Top of concrete
 slab reo
 Top flange
 Web
 Bottom flange
 Δx

R_{cc}
 $R_{rs, reo}$
 $R_{rs, tr}$
 $R_{rs, w}$
 $R_{rs, bf}$
 $R_{rs, total}$



All steel tension forces are calculated for their design elevated temperatures

THE UNIVERSITY OF AUCKLAND
 FACULTY OF ENGINEERING


UC UNIVERSITY OF CANTERBURY
 Te Whare Wananga o Waitaha


Step 10: Comparison of SPM Prediction with FEM for Real Floor System 2004/2005

- First analysis of a complete floor system
- 550m² 19 storey building built 1990
- Trapezoidal decking on secondary beams with central primary beam
- Floor divided into two slab panels
- This design example has been given in each edition of the procedure to keep a benchmark on the impacts of development of the model





Reflected Floor Plan






25





Step 11: Distribution of Slab Panel Loads into Supporting Members for Strength Determination 2005

- Based on yieldline pattern but with modifications from 2013 study: see application slides for changes
- This loading must be sufficient to avoid support beam failure and subsequent slab panel plastic collapse (Abu)
- FEM modelling showed that the two way deformation pattern is more realistic than ambient temperature design practice




	G+Q			Fire - 44min		
	Hand calc.(HC)	ABAQUS (ABQ)	((ABQ-HC)/ABQ)*100	SPM	ABAQUS	((ABQ-SPM)/ABQ)*100
Column-1 (A-5)	64.8	43.5	-49.0%	55.0	71.8	23.4%
Column-2 (B-5)	159.9	180.2	11.3%	148.8	130.0	-14.5%
50% of Column A-4	18.9	29.6	36.1%	32.6	31.2	-4.5%
Total	243.6	253.3	3.8%	236.4	233.0	-1.5%






26



Step 12: Including Length of Structural Fire Severity on Limiting Deflection 2005/2006

Slab panel central vertical downwards deflection versus time shows three stages of behaviour in fire:

- Stage 1: Decreasing rate of deflection with time due to thermal effects
- Stage 2: Constant rate of deflection with time due to loss of yieldline capacity balanced by enhanced tensile membrane resistance. Some surface cracks in slab due to loss of moisture from concrete
- Stage 3: Increasing rate of deflection with full depth cracks(s) forming and ultimately fracture of reinforcement crossing the crack(s)



Step 12: Including Length of Structural Fire Severity on Limiting Deflection 2005/2006

Time of standard fire exposure

Midspan vertical deflection

Flat slab

Slab on secondary beams

Failure


Failure

Stage 1

Stage 2



Stage 3

SPM gives design capacity towards end of stage 2 behaviour; included through the C_{ISO} factor




Step 13: Third Edition Published 2006


- Peer reviewed internationally
- Now used in most multi-storey composite steel floor fire engineered buildings in New Zealand
- This workshop presents the next revision to the third edition (ie the fourth edition)



Input screen 2006 edition




Output screen 2006 edition



Step 14: Incorporating Orthotropic Reinforcement Conditions into Tensile Membrane Model 2008/2009

- Undertaken by AP Tony Gillies, Lakehead University, Canada and graduate students
- Incorporates tensile membrane model updates from Bailey
- All applications are orthotropic due to temperature gradient effects even in regular slabs



THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING


UC
UNIVERSITY OF CANTERBURY
To Whare Wananga o Waitaha

31

SCNZ STEEL CONSTRUCTION NEW ZEALAND

Step 15: Improving the Accuracy of the Tensile Membrane Model 2009

- Correct orientation of tensile membrane fracture plane
 - tensile membrane fracture may be in L_x or L_y direction
 - whichever is the weaker
- Maintaining equilibrium at yieldline intersections
 - Steel across yieldlines cannot be above yield



THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING

UC
UNIVERSITY OF CANTERBURY
To Whare Wananga o Waitaha

32

SCNZ STEEL CONSTRUCTION NEW ZEALAND

Step 16: Consideration of "double dipping" in regard to tension action in slab panel

- Can tension action in reinforcement and beams be used in yieldline moment and tensile membrane enhancement?
- Yes, until a full height fracture crack opens up along a yieldline

If $R_{tsy} < R_{tsx}$ (long direction weaker):

- Final fracture not along yieldline
- No loss of yieldline moment capacity due to tensile membrane action

If $R_{tsx} < R_{tsy}$ (short direction weaker):

- Final fracture along yieldline CD
- Loss of yieldline moment capacity near final collapse
- Beyond time to failure predicted from method

THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING

UC
UNIVERSITY OF CANTERBURY
To Whare Wananga o Waitaha

33

SCNZ STEEL CONSTRUCTION NEW ZEALAND

Step 17: Including Limitation Based on Compression Failure of Concrete Compression Ring 2010

- Avoidance of concrete compression failure in edge of slab
- Calculation of design width of concrete in compression
- Ensuring this is not also included in composite slab contribution to supporting beam
- More on this in the application slides

THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING

UC
UNIVERSITY OF CANTERBURY
To Whare Wananga o Waitaha

34

SCNZ STEEL CONSTRUCTION NEW ZEALAND

Step 18: Critical Review of Design Temperatures of Unprotected Secondary Beams within Slab Panel and SPM Deflection Limits 2011


4th year student project in 2011

Objectives:

1. Review temperatures used for unprotected steel beams in SPM 2006 against 6 recent large scale fire tests
2. Review relationship between fire gas temperature and steel beam temperature against same 6 tests
3. Review calculated deflections against test deflections
4. Make recommendations for changes to SPM 2006 criteria

Tests used:


1. Cardington Demonstration Furniture Test 1995
2. Cardington Corner Test 1995
3. Cardington Corner Test 2003
4. Mokrsko
5. FRACOF
6. COSSFIRE



Step 18: Critical Review of Design Temperatures of Unprotected Secondary Beams within Slab Panel and SPM Deflection Limits 2011



Fire test	$\phi_{fire}W_u$ kPa	W^*_{test} kPa	$W^*_{test}/\phi_{fire}W_u$	Δ_{limit} mm	Δ_{test} mm	$\Delta_{test}/\Delta_{limit}$	t_{eq} mins	Notes on t_{eq}
Cardington Furniture Test	7.09	4.94	0.7	726	642	0.88	54	Calculated from $t_{eq} = e_f k_D W_f$
Cardington Corner Test	6.47	4.94	0.76	754	388	0.51	62	Calculated from $t_{eq} = e_f k_D W_f$
Cardington 2003 Test	5.25	7.15	1.36	777	919	1.18	57	Calculated from $t_{eq} = e_f k_D W_f$
Mokrsko Test	7	6.6	0.94	864	892	1.03	65	Calculated from $t_{eq} = e_f k_D W_f$
FRACOF Test	19.55	6.89	0.35	750	460	0.61	120	Duration heating curve in furnace
COSSFIRE Test Option 1 (Note 1)	8.91	6.41	0.72	668	465	0.7	120	Duration heating curve in furnace
COSSFIRE Test Option 2 (Note 1)	4.19	6.41	1.53	668	465	0.7	120	Duration heating curve in furnace
Average value of 6 tests			0.81			0.82		

Note 1: The COSSFIRE test panel underwent a support failure of one short edge supporting beam. The first option is the SPM calculation on the basis of all support beams effective. The second option is the SPM calculation on the basis that one L_x support beam is ineffective and therefore the slab panel length L_x is doubled as that support becomes an effective centreline of a larger panel.



Step 19: Rewriting of SPM Software 2011 to 2012

- Much more user-friendly input/output
- Written in current version Visual Basic
- Data input screens include diagrams and explanatory text
- Currently in beta version
- QA over 2012/2013 summer with ongoing QA 2013/2014
- Incorporates all stages of development
- Demonstration to follow



Step 20: Comparison of SPM with Other Desktop Based Computer Programs for Composite Floor System Design

- Summer research project 2012/2013 (Daniels 2013)
- Comparison SPM, MACS+, TSLAB
- Conclusions:
 - SPM is the most comprehensive and technically accurate
 - SPM is the only one including detailing requirements
 - SPM and TSLAB bases design adequacy on structural fire severity (t_e)
 - MACS+ bases design adequacy on either structural fire severity or parametric time temperature fire exposure

Step 21: Strength and Stiffness of Slab Panel Edge Support Beams

- Part 4 Student Project 2013 (Su, Zhang, 2013)
- Also MEFE project
- Findings:
 - Slab panel support beams must have sufficient strength and stiffness to avoid a plastic collapse mechanism
 - Maximum support beam deflection < span/75 for effective slab panel support
 - Some changes to support beam loading
 - See application slides



Step 22: Modification to Slab Panel Deflection Limits

The deflection limits given in HERA Report R4-131 equations A23.3, A23.4 and A23.6 are modified to the following:

$$\Delta_{limit} = \left[\min(\Delta_1; \Delta_2) - 0.5 \left(\frac{L_{xb}}{100} + \frac{L_{yb}}{100} \right) \right] C_{ISO} \leq L_x / 15$$

Revised A23.3

$$C_{ISO} = 0.0074 t_{eq} + 0.63 \geq 0.9$$

Revised A23.4

$$\Delta_{max} = \min(\Delta_1; \Delta_2) C_{ISO} + \Delta_{spsb}$$

Revised A23.6



Step 22: Reasons for deflection limit modifications

- Eqn A23.3 – slab panel support beam deflection reduces tensile membrane enhancement; based on average deflection along parabolic deflected shape
- Eqn A23.3 – span/15 is slightly less than limit that has been tested to without failure
- Eqn A 23.4 – see details in (Wu et al, 2012)
- Eqn A23.6 – gives total deflection that floor may reach for determining required clearance underneath for fire separating walls running under middle of slab panel

Potential Future SPM Related Research

Contribution of Long Span Beams with Continuous Web Openings to Slab Panel Resistance

- These are becoming more common
- Status:
 - web contribution currently ignored
 - bottom flange laterally buckles
 - is this accurate?
- Need student and funding



Slab Panel Performance with Steel Fibre Reinforcement

- General determination following on from 2011 research
- Status:
 - Linus Lim in 2000 undertook PhD 6 slab panel tests and procedure verification
 - Repeat tests with fibres instead of general mesh
 - These used in conjunction with additional support reinforcement?

Determining the Adequacy of Slab Panel Detailing Provisions

- Determine by large scale experimental testing or modelling the adequacy of the current SPM detailing provisions
- Three large scale fire tests have recently supported the need for these with premature failures when details not included:
 - Mokrsko: slab pulled off slab panel edge support beam due to lack of edge and anchor bars around shear studs
 - Fracof: fracture of mesh where not adequately lapped within slab panel
 - VUT: shear failure at interior support where interior support bars too short and wrongly placed
- Planned second VUT test imminent that will test some of these provisions further especially the strength and stability of support beam requirements

References

References 1 of 4

- AS/NZS1170.0 2002. Structural Design Actions Part 0 - General Principles. In: STANDARDS, N. Z. (ed.). Wellington, NZ: Standards New Zealand.
- BAILEY, C. G. 2000. *Design of steel members with composite slabs at the fire limit state*, Building Research Establishment.
- BAILEY, C. G. 2003. Efficient Arrangement of Reinforcement for Membrane Behaviour of Composite Floor Slabs in Fire Conditions. *Journal of Constructional Steel Research*, 59, 931 - 949.
- BRIKIS, A., GREGORY, T., HILL, C. & MINOR, T. 2010. *Modeling of Reinforced Concrete Slabs Under Fire*. Lakehead University.
- CLIFTON, G. C. 2006. Design of composite steel floor systems for severe fires, HERA Report R4-131. Manukau City: New Zealand HERA.
- CLIFTON, G. C. & BECK, C. 2002. Revision of the Slab Panel Method - Comparison With Experimental Results. *Steel Design and Construction Bulletin*, 70, 1 - 19, 47.
- CLIFTON, G. C. & BECK, C. 2003. Design of Multi-Storey Steel Framed Buildings with Unprotected Secondary Beams or Joists for Dependable Inelastic Response in Fires: Second Edition. *Steel Design and Construction Bulletin*, 71, 3 - 72.
- CLIFTON, G. C., HINDERHOFER, M. & SCHMID, R. 2001. Design of Multi-Storey Steel Framed Buildings with Unprotected Secondary Beams or Joists for Dependable Inelastic Response in Severe Fires. *Steel Design and Construction Bulletin*, 60, 1 - 58.

References 2 of 4

- ENV1991-1-2 2002. Eurocode 1: Actions on Structures Part 1-2: General Actions - Actions on Structures Exposed to Fire. In: CEN (ed.). CEN, Brussels, Belgium.
- HUANG, Z., BURGESS, I. W. & PLANK, R. J. 2003. Modelling Membrane Action of Concrete Slabs in Composite Action in Fire, Theoretical Development and Validations. *ASCE Journal of Structural Engineering*, 129, 1093 - 1112.
- ISO834 1999. Fire Resistance Tests - Elements of Building Construction Part 1 General Requirements. In: ISO, G., SWITZERLAND (ed.). ISO, Geneva, Switzerland.
- KIRBY, B. 1998. The Behaviour of a Multi-Storey Steel Framed Building Subject to Fire Attack-Experimental Data: Also data from BRE, Cardington, on the Corner Fire Test and the Large Compartment Fire Test, 1996. Swinden: British Steel Swinden Technology Centre.
- LI, Y. & WU, M. Year. Temperatures in Steel Beams in Office Building Fires. In: University of Auckland Civil Engineering 4th Year Projects, 2011 Auckland. Auckland.
- LIM, L. & WADE, C. A. 2002. Experimental Fire Tests of Two-Way Concrete Slabs, Fire Engineering Research Report 02/12. Christchurch, NZ: University of Canterbury.
- MAGO, N. 2004a. Influence of slab panel edge sagging in fire - Stage 2 of the SPM: Concise summary, HERA Report R4-118.1. Manukau City, NZ: New Zealand HERA.

References 3 of 4

- MAGO, N. 2004b. FEA of three WRCSI fire tests: concise summary, HERA Report R4-118.2. Manukau City, NZ: New Zealand HERA.
- MAGO, N. 2004c. Composite floor system performance in ISO 100 min and natural fire test 44 min: concise summary, HERA Report R4-118.3. Manukau City, NZ: New Zealand HERA.
- MAGO, N. 2005. DCB No 71 with secondary beams or Speedfloor joists: concise summary, HERA Report R4-118.4. Manukau City, NZ: New Zealand HERA.
- MAGO, N. & CLIFTON, G. C. 2003. Stage 2 development of the Slab Panel Design Method, HERA Report R4-118. Manukau City, NZ: New Zealand HERA.
- MAGO, N. & CLIFTON, G. C. 2005. Advanced Analysis of Slab Panel Floor Systems Under Severe Fire Attack. *Steel Design and Construction Bulletin*, 77, 3 - 18, 23 - 24.
- MOSS, P. J. & CLIFTON, G. C. 2004. Modelling of the Cardington LBTF Steel Frame Building Fire Tests. *Fire and Materials*, 28, 177 - 198.
- PARK, R. 1970. Ultimate Strength of Reinforced Concrete Slabs, Volume 2. Christchurch, New Zealand: The University of Canterbury.

References 4 of 4

- SPEARPOINT, M. E. (ed.) 2008. *Fire Engineering Design Guide, Third Edition*, Christchurch, NZ: Centre for Advanced Engineering.
- WALD, F. & KALLEROVA, P. 2009. Draft Summary of Results from Fire Test in Mokrsko 2008. Prague, Czechoslovakia: CVUT.
- WU, C. LI, T. and CLIFTON G. C. *Temperature and Fire Resistance of Unprotected Steel Beams in Typical Office Building Fires. Part 4* Project 2011, Department of Civil Engineering, University of Auckland, 2012
- LIM Z.Y. *Slab Panel Program in Severe Fire*. Summer Research Project, Department of Civil Engineering, University of Auckland, 2012
- DANIELS, J. *Comparison of the Slab Panel Method with other Desktop Computer Floor System Fire Design Programs*. Summer Research Project, Department of Civil Engineering, University of Auckland, 2013
- SU, M. *Strength and Stability of Slab Panel Support Beams. Part 4* Project 2013, Department of Civil Engineering, University of Auckland, 2013.
- ZHANG, B. *Strength and Stability of Slab Panel Support Beams. Part 4* Project, Department of Civil Engineering, University of Auckland, 2013.


THE END

THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING

UC
UNIVERSITY OF
CANTERBURY
Te Whare Wananga o Waitaha
UNIVERSITY OF NEW ZEALAND


51

SCNZ STEEL CONSTRUCTION
NEW ZEALAND




Modifications to the Application of the SPM:2006 Edition and Application to C/VM2

By G Charles Clifton,
University of Auckland
and
Anthony Abu
University of Canterbury





1




Scope of Presentation

These slides cover:

- Changes to 2006 edition regarding implementation
- How to implement new software: this is covered by worked examples in second half of presentation
- Modification of HERA Report R4-131: 2006



2




SPM software

- Major Rewrite
- Much more user-friendly
- Multiple input screens
- Diagrams to guide determination of input
- Expanded printed output

The top screenshot shows a structural analysis model with various slab panels and reinforcement details. The bottom screenshot shows a detailed output report with columns for description, units, and values.

UNIVERSITY OF
CANTERBURY
Te Whare Wananga o Waitaha
Christchurch New Zealand

3



Detailing of Slab Panel Reinforcement: 2 of 2


Reasons for Changes:

- Trimmer bar length increased to suppress shear fracture near supports observed in large scale Australian (VU) fire test
- Layout of trimmer bars in corners modified so only one layer specified; otherwise too much congestion of reinforcement
- Ductile mesh is now standard practice and can be used as interior support bars



Increased Loading on Slab Panel Support Beams Along Edges of Building: 1 of 2

Slab panel support beams along the edges of a building require enhanced loading as shown. Applies to beams at the physical edge of a slab.



Increased Loading on Slab Panel Support Beams Along Edges of Building: 2 of 2

Reasons for Changes:


- Study on slab panel stability 2013 (Su, Zhang 2013) showed edge beams designed for loads based on yield line tributary area start to form plastic collapse mechanism before the specified FRR (time equivalent) period is achieved.
- Only an issue for edge beams; slab panel interior support beams can be designed for loading from slab panel yield line tributary area


Restraint from End Connections to Slab Panel Support Beams


- Deflection of support beams $< \text{span}/75$
- Simple connections cannot develop moment resistance to the beam in fire
- Semi-rigid and rigid connections can develop moment capacity based on same load paths as for ambient temperature design

Suppression of Concrete Slab Edge compression failure: 1 of 3


- Tensile membrane action can generate concrete compression failure at middle of long edge
- Concrete slab in this region may also be resisting composite action from slab panel support beam
- Need to account for both effects to avoid overstressing concrete








9



Suppression of Concrete Slab Edge compression failure: 2 of 3





Output from SPM

Concrete compression check	
C _c	954 kN
C _{cr}	314 kN
T _{cr}	319 °C
a _{c,sp}	256 mm


The concrete passed the compression test

C_c = compression force from tensile membrane action
 C_{cr} = compression carried by compression reinforcement
 a_{c,sp} = depth of concrete compression stress block generated by tensile membrane action < that associated with compression failure





10



Suppression of Concrete Slab Edge compression failure: 3 of 3

Concrete stress block due to tensile membrane action

$a_{c,sp}$ DH 10 or 12 edge bar, with standard hook
(to-hrc/2)

40 mm (typical)

Mesh

Steel deck

Optional deck trough bars




Primary edge beam

x direction

Concrete fibre in maximum compression

Compression reinforcement (optional) - generates C_{cr}

If the support beam is resisting the loads by composite action then $a_{c,sp}$ must be deducted from the effective width of the concrete slab required for composite action as the compression from each is generated by different mechanisms and is additive. This is where the compression reinforcement can be placed to resist the tensile membrane induced compression.








References for SPM Modifications to Application

SU, M. *Strength and Stability of Slab Panel Support Beams*. Part 4 Project, Department of Civil Engineering, University of Auckland, 2013.

ZHANG, B. *Strength and Stability of Slab Panel Support Beams*. Part 4 Project, Department of Civil Engineering, University of Auckland, 2013.

LIM Z.Y. *Slab Panel Program in Severe Fire*. Summer Research Project, Department of Civil Engineering, University of Auckland, 2012.

Application to C/VM2

- SPM is a design procedure based on resistance to fully developed fire
- Three options for fully developed fire given by C/VM2. These are:
 1. Use a time equivalent formula and ensure $FRR \geq t_e$
 2. Use a parametric time versus gas time temperature formula to generate gas time – temperature conditions for input into a structural response model
 3. Construct a Heat Release Rate versus time design option then generate gas time – temperature conditions for input into a structural response model
- SPM is used with the first option; or with a FRR from the C/AS set of Approved Documents

Modifications Proposed to C/VM2: 1 of 4

- A new joint Australasian Composite Standard, AS/NZS 2327, is under development.
- Draft for public comment due for completion end 2014
- New section 6 on fire proposes two important modifications to C/VM2. These are as detailed on the next 3 slides

Modifications Proposed to C/VM2: 2 of 4

First modification is to the time equivalence equation:

$$t_e = e_{f,\text{mod}} k_b k_m w_f$$

No 20 minute minimum value for steel or composite steel/concrete members

Reasons for first modification:

1. The equations have been developed for protected steel
2. The k_m factor accounts for the faster heating rate of unprotected steel
3. There is no modification in the Eurocode application of t_e
4. C/VM2 applies it to other materials for which a modification may be appropriate

Modifications Proposed to C/VM2: 3 of 4

Modification to the fire load modification factor, F_m , used to calculate $e_{f,\text{mod}}$ used in the t_e equation

Remove the distinction on ductility (all steel structures designed and detailed to our earthquake requirements will have dependable deformation capacity in fire)


Replace with :

- $F_m = 1.0$ for unsprinklered buildings
- $F_m = 0.5$ for sprinklered buildings where the fires are localised and the fire load is not more than 400 MJ/m² floor area (examples are car park fires, hotels and motels)
- $F_m = 0.5$ for other sprinklered buildings with an escape height of $\leq 10\text{m}$
- $F_m = 0.75$ for other sprinklered buildings with an escape height $> 10\text{m}$ but $\leq 25\text{m}$.
- $F_m = 1.0$ for other sprinklered buildings with an escape height $> 25\text{m}$



Modifications Proposed to C/VM2: 4 of 4


Reasons for proposed F_m modifications:

1. This should be a modification only to the loadings side of the $S^* \leq \phi R_u$ equation
2. With sprinklers, the fire load can be taken as the "arbitrary point in time" (APT) fire load to be used if sprinklers don't suppress the developing fire
3. The APT fire load is typically 0.6 to 0.75 x the 80% fire load
4. For buildings with isolated fires, benefit of the localised nature of the fire is also recognised in $F_m = 0.5$
5. For low-rise buildings, some benefit of Fire Service intervention is included in reduction to $F_m = 0.5$
6. Where fire service can reach floors from the outside, upper value of fire load from 3 is proposed, ie $F_m = 0.75$
7. Above that height, no reduction in fire load applies, ie. $F_m = 1.0$




THE END




THE UNIVERSITY OF AUCKLAND
FACULTY OF ENGINEERING



UC
UNIVERSITY OF CANTERBURY
To Whero Wānanga o Waitaha
Christchurch, New Zealand

18



SCNZ STEEL CONSTRUCTION
NEW ZEALAND